

| 产品型号 Products Codes | 材质 聚酯 Material | 后处理方式 Post-Processing | 克重 Weight | 厚度 Thickness | 强度 (N/5CM) Tensile Strength | | 伸长率 % Elongation | | 破裂强度 M. Burst | 压差 Pressure Drop | 过滤效率 Filtration Efficiency | 工作温度℃ Continuous Serve Temp. | 防油/水 Water/Oil Proof | 阻燃 Fire Proof | 防静电 Anti- Statics | 高效 High Efficiency |
|------------------------|----------------------|---|--------------|-----------------|--------------------------------|-----|---------------------|----|------------------|---------------------|-----------------------------------|------------------------------------|----------------------------|---------------------|-------------------------|--------------------------|
| | | | G/SQM | MM | MD | CD | MD | CD | Kpa | 32L/0.1M2.M | % (µm: Micron) | | | | | |
| 260WOP | PET 100% | Water & Oil Proof | 265 | 0.62 | 1160 | 700 | 39 | 36 | 2850 | 50 Pa | > 99% @5µm | 120 | OK | / | / | / |
| 260HPTFE | PET 100% | PTFE Hot-laminated | 265 | 0.58 | 1160 | 700 | 39 | 36 | 2850 | 320 Pa | > 99% @0.3µm (H11-13 Optional) | 135 | / | / | / | OK |
| 260WOP-PTFE | PET 100% | Water & Oil Proof + PTFE laminated | 270 | 0.64 | 1160 | 700 | 39 | 36 | 2850 | 260 Pa | > 99% @0.3µm (H11-13 Optional) | 120 | OK | / | / | OK |
| 260AS-AL | PET 100% | Aluminum coat (anti-static) | 265 | 0.62 | 1160 | 700 | 39 | 36 | 2850 | 50 Pa | > 99% @5µm | 120 | / | / | OK | / |
| 260AS-AL-PTFE | PET 100% | Aluminium Coated (anti-static) + PTFE laminated | 270 | 0.63 | 1160 | 700 | 39 | 36 | 2850 | 260 Pa | > 99% @0.3µm (H11-13 Optional) | 120 | / | / | OK | OK |
| 260FR | PET 100% | Flame-Retardant | 280 | 0.62 | 1160 | 700 | 39 | 36 | 2850 | 50 Pa | > 99% @5µm | 120 | / | OK | / | / |
| 260FR-HPTFE | PET 100% | Flame-retardant, & PTFE Hot-laminated | 285 | 0.58 | 1160 | 700 | 39 | 36 | 2850 | 320 Pa | > 99% @0.3µm (H11-13 Optional) | 135 | / | OK | / | OK |
| 260CA | PET 100% | Carbon coated, Acid Gas Resist (Black Color) | 265 | 0.62 | 1160 | 700 | 39 | 36 | 2850 | 50 Pa | > 99% @5µm | 120 | / | / | OK | / |



Material Colour can be customised. If no special requests, the basic colour is white.

Spunbonded PET filtration material is widely used in industrial filtration, applied with different post-processing treatments, various functions achieved with excellent performances.

Hefei Really Purifying Equipment Co. Ltd

Website: <https://www.filter-making.com> Email: exp@filter-making.com